

## Specifications Sheet



### Motorola Canopy 25 pack of 5.4 GHz Lite SM



Canopy Part Number	5460SM
Description	25 pack of 5.4 GHz Lite SM
Signaling Rate	10 Mbps, 20 Mbps with Advantage AP
Typical LOS Range	3.2 km (2 Miles)
Typical Aggregate Useful Throughput	512 kbps, 768 kbps burst 100 kbps full duplex CIR
Frequency range of band	U-NII 5470-5725 MHz
Channel Width	20 MHz
Modulation Type	High Index 2-level and 4-level Frequency Shift Keying (FSK) optimized for interference rejection
Channel Spacing	configurable on 5 MHz increments
Encryption	DES capable
Latency	5 - 7 msec
Carrier to Interference ratio (C/I)	-3dB @ 10 Mbps, -10dB @ 20 Mbps at -65dBm
Nominal Receiver Sensitivity (dbm typical)	-86 dBm
Antenna Gain (dB)	7 dBi
EIRP (dB)	Adjustable to 30 dBm
Equivalent Isotropic Radiated Power (EIRP)	Adjustable to 1 W
DC Power (typical)	0.3A @ 24VDC = 7.2 W
Antenna Beam Width	3 dB antenna beam width 60 degrees, azimuth and elevation
Mean Time Between Failure (MTBF)	40 year
Temperature	-40° C to +55° C (-40° F to +131° F)
Wind Survival	190 km/hr (118 miles/hr)
Dimensions	11.75 in H x 3.4 in W x 3.4 in D (29.9 cm H x 8.6 cm W x 8.6 cm D)
Weight	.45 kg (1 lb)
Access Method	Time Division Duplexing/Time Division Multiple Access (TDD/TDMA)
Interface	10/100 Base T, half/full duplex. Rate auto negotiated (802.3 compliant)
Protocols Used	IPV4, UDP, TCP, ICMP, Telnet, HTTP, FTP, SNMP
Network Management	HTTP, TELNET, FTP, SNMP Version 2c
CE	"CE" marked & compliant to EN301 893, Implements DFS & TPC. DoCs are available at <a href="http://www.canopywireless.com/doc.php">http://www.canopywireless.com/doc.php</a>

Specifications subject to change without notice.